



The Choice of Professionals

Ruco® Ready Mixed Joint Compound is a non-asbestos, ready-to-apply formulation for embedding drywall tape reinforcement, fasteners, metal corner beads and drywall trims over wallboard. Ready Mixed Joint Compound may also be used for filling, leveling and finishing coats, skim-coating entire wallboard surfaces, and applying simple textures.



RUCO® All Purpose Ready Mixed Joint Compound

ADVANTAGES

VACUUM PROCESSED:

A process that removes crater-causing air bubbles and reduces the need for costly sanding and over-coatings. A smooth surface can be achieved with fewer swipes since there is no entrained air to form craters or fish eyes on the surface.

LOW SHRINKAGE AND CRACK

RESISTANT: Compound ideal for heavy fill because of its low shrinkage, excellent adhesion and crack resistance.

CONSISTENT PRODUCT TIME

AFTER TIME: Satisfied customers continually report that Ruco® Joint Compounds are highly consistent from batch to batch. This is achieved through precise internal procedures and quality control.

PRECAUTIONS:

If dry-sanding or otherwise working in a dusty environment containing this material, ventilate or use a dust collector. It is also recommended that eye protection and a respirator, which is NIOSH approved, be worn. Wet sanding or sponging finished joints is recommended to avoid creating dust.

WARRANTY:

Job conditions and methods of application such as: temperature, humidity, and over-thinning are beyond the control of SWP Inc. Its warranties of fitness and merchantability as well as any other warranties expressed or implied shall be effective if this product is applied according to SWP Inc. directions and specifications. Maximum liability shall be limited to replacement of material only.

Customer Service

1-800-554-9255

RUCO®
Southern Wall Products Incorporated
1825 Fellowship Rd
Tucker, Georgia 30084
770-621-3065
www.ruco.com

